



DM1413-3

About FireKing 3 hour Data Safes:

Computer Media is so easily damaged, manufacturers recommend computer media not be exposed to temperatures over 125°F or humidity over 85%. Even a hot mug of coffee represents a real hazard, so imagine what a small fire would do. In a FireKing Data Safe, computer media is protected from fire, dust, magnetic fields, unauthorized access, accidental damage and electrostatics. The walls and doors provide the ultimate in protection by incorporating layers of heat absorbing material, fireproof insulating foam and a tough steel casing. Three-way boltwork ensures the doors remain shut if a building collapses during a fire or if forced entry is attempted.

3-Hour UL Fire Test:

The safe must maintain an interior temperature less than 125°F and an interior relative humidity less than 80% for class 125, when exposed to fire as per the Standard Time Temperature Curve for 3 hours to 1925°F. It must undergo all other requirements for the Fire Endurance Test, the Explosion Hazard Test, the Humidity Test, and the Fire and Impact Test. Basically, no explosion through 30 minutes to exposure to a 2000°F fire and immediate 30 foot drop test and a standard reheating for one hour to 1700°F



DM1413-3 General Specifications:

Exterior Size	29.625"H x 25.25"W x 31"D <i>Add 1.75" for Handle</i>			
Interior Size	13.625"H x 11.5"W X 16.6875"D			
Capacity	1.5 cu. ft.			
Weight	650 lbs			
Interior Options	CM12-FS (Fixed Shelf) CM12-CD (Composite Drawer)			
Fire Rating	UL 3-hour Class 125 Fire & Impact			
Burglary Rating	UL RSC			
Media Capacity {optional Drawers}	Media type	#drawers	media per/drawer	Total capacity
	3.5 Floppy	3	306	918
	CD-ROM:	2	70	140
	IBM 3480	2	28	56
	4mm	4	70	280
	8mm	4	39	156
	DLT	2	24	48
	ZIP disk	3	73	219
Lock	Digital Combination			
Access Angle	Open door 90° for complete access			
Finish	Platinum			
Add'l Testing	Canadian UL Class 52-3-Hour fire & impact rating			

Safetyfile Inc.

23075 Highway 7, Excelsior MN 55331 ph: 800-700-8025 fax: 952-908-3162 email: sales@safetyfile